

imageRUNNER
2224N / 2224

Breeze through Productivity

Simple, Fuss-free and Reliable


Designed with essential features for a seamless everyday workflow, the new imageRUNNER 2224N/2224 delivers robust efficiency by combining usability with functionality.



Seamless Usability

Packed with the essentials to keep workflow a breeze

 Touch Panel


 Ease of Navigation

 Mobile Printing Through Wi-Fi*

*iR2224N Only

Versatile Productivity

Print various materials in-house with improved paper handling

 ID Card/Passport Copy

 Improved Paper Handling

Fortified Security

The latest security for a peace of mind

 Detection & Recovery

 Device & Network Protection

Business Can Be Simple

SPECIFICATIONS

Main Unit	Machine Type	A3 Monochrome Laser Multifunctional
	Core Functions	iR2224N: Print, Copy, Scan and Send iR2224: Print, Copy and Scan
	Control Panel	8.89 cm (3.5 inch) Monochrome Touch Panel
	Memory	Standard: 1.0 GB RAM
	Storage	eMMC: 2 GB
	Interface Connection	NETWORK (only for iR2224N) Standard: 100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) OTHERS Standard: USB 2.0 (Device) x1
	Paper Supply Capacity (A4, 80g/m² (gsm))	Standard: 350 sheets (Paper Drawer: 250 Sheets, MPT Tray: 100 Sheets) Maximum: 600 sheets (with Cassette Feeding Module-AK1)* *iR2224N only
	Paper Output Capacity (A4, 80g/m² (gsm))	Standard: 250 sheets Maximum: 250 sheets
	Supported Media Types	Multi-purpose Tray: Thin, Plain, Recycled, Heavy, Colour, Bond, Label, Pre-punched, Envelope Paper Cassette: Plain, Recycled, Colour, Pre-punched
	Supported Media Sizes	Multi-purpose tray: A3, A4, A4R, A5, A5R, B4, B5, B5R, Envelope(COM10, Monarch, DL, ISO-C5), Custom size Min. 95.0 x 148.0 mm Up to 297.0 x 431.0 mm. Paper Cassette: A3, A4, A4R, A5R, B4, B5, B5R
	Supported Media Weights	Multi-purpose tray: 60 to 157g/m ² (gsm) Paper Cassettes: 64 to 90g/m ² (gsm) Duplex: 60 to 90g/m ² (gsm)
	Warm-up Time	From Power On: 13 seconds or less *Time from device power-on, until copy ready (not print reservation) From Sleep Mode: 4.3 seconds or less
	Dimensions (W x D x H)	iR2224N (with DADF): 627 x 607 x 606 mm iR2224/2224N (with Platen cover): 627 x 589 x 502 mm
	Installation Space (W x D)	1065 x 1285 mm
	Weight	iR2224N: Approx. 30.3 kg without toner and platen cover. iR2224: Approx. 31.6 kg without toner and including platen cover.
Print	Print Speed (BW)	1-sided: Up to 24 pages/min. (A4), Up to 12 pages/min. (A3), Up to 11 pages/min. (A4R) 2-sided: Up to 16.7 pages/min. (A4), Up to 7.5 pages/min. (A3), Up to 7.8 pages/min. (A4R)
	Print Resolution (dpi)	600 x 600
	Page Description Languages	Standard: UFR II Optional: PCL6 (iR2224N only)
	Fonts	PCL fonts: 45 Roman, 10 Bitmap fonts
	Operating System	UFR II: Windows®8.1 / Windows®10 / Windows®11 / Windows®Server2012 / Windows®Server2012 R2 / Windows®Server2016 / Windows®Server2019 / Windows®Server2022, macOS (10.12 or later) PCL: Windows®8.1 / Windows®10 / Windows®11 / Windows®Server2012 / Windows®Server2012 R2 / Windows®Server2016 / Windows®Server2019 / Windows®Server2022
Copy	Copy Speed	1-sided: Up to 24 pages/min. (A4), Up to 12 pages/min. (A3), Up to 11 pages/min. (A4R) 2-sided: Up to 16.7 pages/min. (A4), Up to 7.5 pages/min. (A3), Up to 7.8 pages/min. (A4R)
	First-Copy-Out Time (BW)	Platen: Approx. 7.4 seconds or less (A4)
	Copy Resolution (dpi)	600 x 600
	Multiple Choices	Up to 999 copies
	Copy Density	Automatic or Manual (9 Levels)
	Magnification	25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 70%, 100%, 141%, 200%, 400%

Scan	Document Feeder Paper Capacity	50 Sheets 80g/m ² (gsm) Platen: Sheet, Book
	Acceptable Originals and Weights	Document Feeder media weight 1-sided/2-sided continuous scanning: 52 to 105g/m ² (gsm) (BW/CL) *Only single sheet feeding is supported in 37-52 and 105-128g/m ² (gsm)
	Supported Media Sizes	Platen: 297.0 x 431.8 mm Document Feeder: A3, A4, A4R, A5, A5R, B4, B5, B5R Custom size: 128.0 x 148.0 mm to 297.0 x 431.8 mm
	Scan Speed (ipm: BW/CL; A4)	DADF: 1-sided Scanning: 35/25 (300 dpi, Send), 25 (600 dpi, Copy) 2-sided Scanning: 12/8 (300 dpi, Send), 8 (600 dpi, Copy)
	Scan Resolution (dpi)	Scan for Copy: Up to 600 x 600 Scan for Send: (Push) Up to 300 x 600, (Pull) up to 600 x 600
Send	Pull Scan Specifications	ScanGear MF For both TWAIN and WIA Windows®8.1 / Windows®10 / Windows®11 macOS (10.12 or later)
	Destination	iR2224N: Email (SMTP), SMB3.0
	Address Book / Speed Dials	iR2224N: LDAP (50) / Local (300) / One-Touch (296)
	Send Resolution (dpi)	Push (iR2224N): 300 x 600 (SMB/FTP/Email) Pull: 50 x 50, 75 x 75, 150 x 150, 200 x 200, 300 x 300, 400 x 400, 600 x 600 *Colour mode is black and white only
	Communication Protocol	File: SMB3.0 (TCP/IP) Email: SMTP (Send) *iR2224N Only
Environmental	File Format	Standard: TIFF, JPEG, PDF (Compact) *Single Page Only
	Operating Environment	Temperature: 10 - 30°C Humidity: 20 - 80% RH (Relative Humidity)
	Power Source	220-240V 50/60Hz (2.8A)
Paper Supply	Power Consumption	Maximum: Approx. 1,500 W Standby: Approx. 15.5 W Sleep mode: Approx. 0.9 W
	Feeder Options	Cassette Feeding Module-AK1 Paper Capacity: 250 sheets x 1 (80g/m ² (gsm)) Paper Type: Plain, Recycled, Colour, Pre-punched Paper Size: A3, A4, A4R, A5, B4, B5, B5R Paper Weight: 64 - 90g/m ² (gsm) Power Source: Main Unit Dimensions (W x D x H): 581 x 575 x 92 mm Weight: Approx. 5.8 kg
Others	Optional Accessories	Platen Cover Type X, DADF-AY2*, Cassette Unit - AK1*, Duplex Unit - E1*, Heater Kit-M2, Cassette Heater Unit-40, PCL Printer Kit- BP1E*, NPG-59 Toner Black, NPG-59 Drum Unit *Only applicable for iR2224N



Delighting You Always

CANON INDIA PVT. LTD.

Corporate Office: 7th Floor, Tower B, Building #5, DLF Epitome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

imageRUNNER
2425

Canon
Delighting You Always

Small in Size, Not in Functions

PERFECT FOR SMALL AND
MEDIUM BUSINESSES

⌄ 25ppm multi-function device

⌄ Monochrome printing

⌄ 7 inch colour touch panel

⌄ Optimal security

⌄ Flexible mobile support



Business can be

imageRUNNER 2425

Advanced functions made simple

Experience an entry level monochrome multi-function device that offers advanced features in a simplified body.

Boasting a range of comfortable operability and optimal security features, the new imageRUNNER 2425 is the perfect printing solution for small and medium businesses.



Wi-Fi Connect



Scan/ Copy



Mobile Support



Touch Panel



Optimal Security



9 STEPS INTO 1

Seamless Usability

Smooth operation with 7-inch colour UI.

The colour touch panel provides great visibility and functionality, displaying useful information at a glance. A full keyboard support allows for easy interaction and data input.

The user interface is similar to the imageRUNNER ADVANCE series, providing an unified user experience across our products.

Increase efficiency of routine work with a touch.

Customisable buttons provide endless personalisation in combining multiple operation settings into one, streamlining workflow and increasing convenience.

A timeline function provides quick reference to previously executed settings, reducing the need for repeated settings.



Security

Optimal Security

The imageRUNNER 2425 comes with a range of up-to-date security features to prevent information leakage or unauthorised access.

uniFLOW Online/ Online Express



uniFLOW Online Express provides improved security through authentication functions, limiting users and their usage as well as prevent scan destination errors.

Document Security



Documents can be held at the machine with **Force Hold Print** until the user releases the job, preventing information leakage from unattended documents.

Device Verification



Verify System at Start-up checks the validity of the device firmware and applications to prevent unauthorised modifications.



Connectivity

Flexible mobile support

The imageRUNNER 2425 supports a wide range of mobile applications such as Canon PRINT Business, AirPrint™, Mopria® and Canon Print Service.

Print or scan documents even without a computer or a router Wi-Fi connection by connecting directly to the multi-function device.



YOU CAN DOWNLOAD FROM
APP STORE OR GOOGLE PLAY



Easy Digitisation

Scan and print documents efficiently.

An integrated Scan Preview allows quick checks on scanned documents for errors before sending, saving time and reducing the need for rescan.

Scanned data are easily transferable to USB and data can be checked before printing to prevent misprints, speeding up workflow efficiency.

SPECIFICATION

MAIN UNIT	
Machine type	A3 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	7 inch TFT LCD WVGA colour touch panel
Memory	Standard: 2.0GB RAM
Storage	eMMC: 30GB
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Others Standard: USB 2.0 (Host) x3, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80gsm)	Standard: 330 sheets Maximum: 580 sheets (with Cassette Feeding Module-AK1)
Paper output capacity (A4, 80gsm)	Standard: 250 sheets Maximum: 250 sheets
Supported media sizes	Multi-purpose tray: A3, A4, A4R, A5, A5R, B4, B5, B5R, Envelopes (No. 10(COM 10), Monarch, ISO-C5, DL) Custom Size/Free Size: Min. 95.0 x 139.7 mm up to 297.0 x 431.8 mm Paper Cassette: A3, A4, A4R, A5R, B4, B5, B5R
Supported media weights	Multi-purpose tray: 60 to 157 gsm Paper Cassettes: 64 to 90 gsm Duplex: 60 to 90 gsm
Warm-up Time (Quick start mode: ON)	4 Seconds or Less* * Time from device power-on to when key operations can be performed on the touch panel display. From Sleep Mode: 10 seconds or less 12 Seconds or Less* *Time from device power on, until copy ready (not print reservation)
Dimensions (W x D x H)	With Platen Cover-AA1: 627 x 665 x 516 mm With DADF-AZ2: 627 x 692 x 616 mm
Installation Space (W x D)	1,065 x 1,285 mm
Weight	With Platen Cover-AA1: Approx. 34.9kg including toner With DADF-AZ2: Approx. 39.9kg including toner
PRINT SPECIFICATIONS	
Print Speed (BW)	Up to 25 ppm (A4), Up to 12 ppm (A3), Up to 11 ppm (A4R)
Print Resolution (dpi)	600 x 600
Page description languages	Standard: UFR II Optional: PCL6, Adobe®PostScript®3™
Direct Print	Supported file types: RUI: PDF, EPS, TIFF/JPEG, XPS USB Memory/Network Place: PDF, TIFF/JPEG, XPS
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andale Mono WT J/K/S/T ¹ (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ² PS fonts: 136 Roman ¹ Requires optional PCL International Font Set-A1 ² Requires optional Barcode Printing Kit-D1
Operating System	UFR II: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.10 or later) PCL: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019 PS: Windows® 7/8.1/10/Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016/Server 2019, MAC OS X (10.10 or later) PPD: Windows® 7/8.1/10, MAC OS X (10.10 or later)
COPY SPECIFICATIONS	
Copy Speed (BW)	Up to 25 ppm (A4), Up to 12 ppm (A3), Up to 11 ppm (A4R)
First-Copy-Out Time (A4) (BW)	Approx. 7.4 seconds or less
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 9,999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	25% - 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%, 115%, 122%, 141%, 200%, 400%
SCAN SPECIFICATIONS	
Type	Optional: Duplexing Automatic Document Feeder (2-sided to 2-sided) (DADF-AZ2) or Platen Cover (Platen Cover-AA1)
Document Feeder Paper Capacity (80 gsm)	DADF-AZ2: 50 Sheets
Acceptable originals and weights	Platen: Sheet, Book Document Feeder media weight: 1-sided scanning: 37 to 128 gsm (BW/CL) 2-sided scanning: 52 to 128 gsm (BW/CL) Only 1-sheet feeding is supported in 37-52 and 105-128 gsm.

SCAN SPECIFICATIONS	
Supported media sizes	Platen: max. scanning size: 297.0 x 432.0 mm Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R Custom size: 139.7 x 148.5 mm to 297.0 x 432.0 mm
Scan Speed (ipm: BW/CL; A4)	DADF-AZ2: 1-sided Scanning: 35/25 (300 dpi, send), 25/13 (600 dpi, copy) 2-sided Scanning: 12/8 (300 dpi, send), 8/4 (600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: up to 600 x 600 Scan for Send: (Push/Pull, BW) up to 600 x 600 (Push/Pull, CL) up to 300 x 300 Scan for Fax: up to 600 x 600
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA
Supported OS	Windows® 7/8.1/10 Windows® Server 2008/Server 2008 R2/Server 2012/Server 2012 R2/Server 2016
Scan Method	Push scan, Pull scan, Scan to Network, Scan to memory media (USB Memory Key), Scan to Mobile Devices, Scan to cloud-based services (uniFLOW)
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP WebDAV Optional: Super G3 FAX
Address Book	LDAP (2,000)/Local (1,600)/One-touch (200)
Send resolution (dpi)	Push: 100 x 100, 150 x 150, 200 x 100 (Standard), 200 x 200 (Fine), 200 x 400* (SuperFine), 300 x 300, 400 x 400* (UltraFine), 600 x 600* Pull: 75 x 75, 100 x 100, 150 x 150, 200 x 200, 300 x 300, 400 x 400*, 600 x 600* *Only applicable for black and white, even if colour mode is selected.
Communication protocol	File: FTP (TCP/IP), SMB (TCP/IP), WebDAV Email/Fax: SMTP(send), POP3(receive)
File Format	Standard: TIFF (MMR), JPEG*, PDF (Compact, PDF/A-1b, Encrypted), XPS (Compact), PDF/XPS (Device Signature) Optional: PDF (Trace & Smooth), PDF/XPS (User Signature), PDF/XPS (Searchable), Office Open XML (PowerPoint, Word) *Single page only
FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	Sending: A3, A4, A4R, A5 ² , A5R ² , B4, B5 ¹ , B5R ² Receiving: A3, A4, A4R, A5R, B4, B5, B5R ¹ Sent as B4 ² Sent as A4
FAX memory	Up to 30,000 pages
Speed dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Power source	220-240V 50/60Hz 2.7A
Power consumption	Maximum: Approx. 1,500 W Standby: Approx. 22.1 W ¹ Sleep mode: Approx. 1 W ² , Approx. 2 W ³ ¹ Reference value: measured one unit ² Wireless LAN power serve mode OFF ³ Wireless LAN power serve mode ON ^{2/3} Sleep mode is not available in all circumstances due to certain settings.
CONSUMABLES	
Toner Cartridges	NPG-59 Black Toner
Toner Yield (Estimated Yield @ 6% coverage)	Black: 10,200 impressions (A4)
PAPER SUPPLY OPTIONS	
Cassette Feeding Module-AK1	Cassette Feeding Module-AK1 Paper Capacity: 250 sheets (80gsm) Paper Type: Plain, Recycled, Colour, Pre-punched Paper Size: A3, A4, A4R, A5, B4, B5, B5R Paper Weight: 64 to 90 gsm Power Source: Main Unit Dimensions (W x D x H): 581 x 575 x 92 mm Weight: Approx. 5.8kg
OTHER ACCESSORIES	
DADF-AZ2, Platen Cover-AA1, PCL International Font Set-A1, PS Printer Kit-CM1, PCL Printer Kit-CM1, Universal Send Digital User Signature Kit-C1, Universal Send Advanced Feature Set-H1, Barcode Printing Kit-D1, Copy Control Interface Kit-D1, Super G3 FAX Board-BE1, Remote Fax Kit-A1	

Canon
Delighting You Always

SOUTH & SOUTHEAST ASIA REGIONAL HEADQUARTERS

CANON SINGAPORE PTE. LTD.

1 Fusionpolis Place #15-10 Galaxis, Singapore 138522
Tel: 65-6799-8888 | Fax: 65-6799-8882 | <https://asia.canon>

DEALER'S STAMP

This document is for information purpose only and the contents are subject to change without notice. Product options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations with respect to this document. Canon and Business Can Be Simple are trademarks of Canon Inc. and/or its affiliates. Other names may be the trademarks for their respective owners.

0221W248 © 2020 Canon Singapore Pte. Ltd. All rights reserved. Printed in Singapore.

imageRUNNER
C3326

Canon
Delighting You Always

ELEVATING WORKSPACE PERFORMANCE

Functional and Efficient



Touch
Panel



Print/Copy/
Scan/fax



Mobile
Support



Wi-Fi
Connectivity



Optimal
Security

Business Can Be Simple

ENHANCING WORKSPACES



EASE OF ACCESSIBILITY

Tap into a rich variety of functions through the built-in 177.8 mm (7 in) operation panel, which is fully customisable to accommodate for organisation of commonly used processes. The Timeline feature displays past job histories which can be conveniently re-executed at a touch, making processes easy for users who repeatedly utilise the same functions and settings.



EFFICIENT DOCUMENT SCANNING

Ensure optimal readability and orientation of scanned documents with the Scan Preview function. Simply review scanned items on the display to rectify any scanning errors before sending, saving time and providing added convenience.

EFFORTLESS DOCUMENT HANDLING

The new multi-functional device offers various finishing options to further ease workflow. Select from ECO-staple, Staple-On-Demand and hole-punching functions that reduces the need for manual collating and stapling.

8
SHEETS

ECO-STAPLE

Up to 8 sheets
(A4/80g/m² (gsm))

50
SHEETS

STAPLE-ON-DEMAND

Up to 50 sheets
(A4/80g/m² (gsm))



SECURE DATA PROTECTION

Worry less about data being compromised using advanced and up-to-date security features in the imageRUNNER C3326. Keep documents safe with authentication and encryption.

Securing Document Access

Manage important or confidential documents securely to prevent leakage of information. The Force Hold Print feature holds the documents at the device and releases it only upon authentication, preventing accidental or unwanted access.



Encrypted PDF to prevent leakage of information

Preventing Risks

Scanned documents in formats like PDF or XPS can be encrypted to secure their digital data with an additional layer of protection alongside limiting access only to the right document handler.



User authentication features to manage access

uniFLOW Online/ Online Express

The imageRUNNER C3326 offers login authentication with uniFLOW Online Express, providing additional document security functions while granting access only to permissible users.



Specifications

MAIN UNIT	
Machine Type	A3 Colour Laser Multifunctional
Core Functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	177.8 mm (7in) TFT LCD WVGA Colour Touch panel
Memory	Standard: 2.0GB RAM
Storage	Standard: 64GB eMMC (available space 30GB) Optional: 256GB SSD
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11 b/g/n) Others Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80g/m ² (gsm))	Standard: 1 200 sheets (100 sheets Multi-purpose tray, 2 x 550 sheets paper cassette) Maximum: 2 300 sheets (with Cassette Feeding Unit-AW1)
Paper Output Capacity (A4, 80g/m ² (gsm))	Standard: 250 sheets Maximum: 645 sheets (with Inner Finisher-L1 and Copy Tray-T2)
Supported Media Types	Multi-purpose tray: Thin, Plain, Heavy, Recycled, Coated ¹ , Colour, Tracing, Bond, Transparency, Labels, Pre-punched, Letterhead, Envelope, Postcard ¹ SRA3 is unsupported for Coated (257 to 300g/m ² (gsm)) Upper Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope ¹ , Postcard ¹ Envelope Feeder Attachment Kit B (standard) is required except ISO-C5. Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope ¹ , Postcard ¹ Envelope Feeder Attachment Kit A (standard) is required.
Supported Media Sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelopes: ISO-C5 Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes ¹ : COM10 No.10, Monarch, DL ¹ Envelope Attachment A (standard) is required.
Supported Media Weights	Multi-purpose tray: 52 to 300g/m ² (gsm) ¹ ¹ SRA3 is unsupported for Coated (257 to 300g/m ² (gsm)). Paper weight supported with Media Adjustment Kit-A1: 60 to 300g/m ² (gsm). Upper/Lower Cassette: 52 to 256g/m ² (gsm) Duplex: 52 to 220g/m ² (gsm)
Warm-up Time (Quick start mode: ON)	4 s or Less ¹ ¹ Time from device power on to when copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 10 s or less From Power On: 10 s or less ¹ ¹ Time from device power-on, until copy ready (not print reservation)
Dimensions (W x D x H)	With Platen Cover-Y3: 565.0 x 659.0 x 788.0 mm With DADF-BA1: 565.0 x 687.0 x 891.0 mm
Installation Space (W x D)	Basic: 978 x 1 088 mm (with Platen Cover-Y3 + right door & multi-purpose tray opened + paper cassette opened) Fully Configured: 1 286 x 1 116 mm (with DADF-BA1 + Inner Finisher-L1 + Copy Tray-T2 extended + paper cassette opened)
Weight (Including toner)	With Platen Cover-Y3: Approx. 71 kg With DADF-BA1: Approx. 78 kg
PRINT SPECIFICATIONS	
Print Speed (BW)	1-sided: Up to 26 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R)
Print Resolution (dpi)	600 x 600, 1 200 x 1 200 (half-speed)
Page Description Languages	Standard: UFR II Option: Adobe PostScript 3, PCL6
Direct Print (RUI)	PDF, EPS, TIFF/JPEG and XPS
Printing from Mobile and Cloud Applications	AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ¹ (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ² ¹ Optional PCL International Font Set-A1 is required. ² Optional Barcode Printing Kit-D1 is required.
Operating System	UFR II: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS(10.13 or later) PCL: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022 PS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS(10.13 or later) PPD: Windows® 10/11, macOS(10.13 or later)

COPY SPECIFICATIONS	
Copy Speed (BW/CL)	1-sided: Up to 26 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R)
First-Copy-Out Time (A4, BW/CL)	Approx. 7.0/8.7 s or less
Copy Resolution (dpi)	600 x 600
Multiple Copies	Up to 999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100%(1:1), 115%, 122%, 141%, 200%, 400%
SCAN SPECIFICATIONS	
Type	Option: Platen Cover-Y3 or DADF-BA1(2-sided to 2-sided)
Document Feeder Paper Capacity (80 gsm)	Up to 100 sheets
Acceptable Originals and Weights	Platen: Sheet, Book and 3-Dimensional objects Document Feeder media weight: 1-sided scanning: 38 to 128g/m ² (gsm) (BW), 64 to 128g/m ² (gsm) (CL) 2-sided scanning: 50 to 128g/m ² (gsm) (BW), 64 to 128g/m ² (gsm) (CL) Platen: Max. scanning size: 297.0 x 431.8 mm
Supported Media Sizes	Document Feeder media size: A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 128.0 x 139.7 mm to 297.0 x 431.8 mm
Scan Speed (ipm: BW/CL; A4)	DADF-BA1: 1-sided Scanning: 70/70 (300 x 300 dpi, send), 51/42 (600 x 600 dpi, copy) 2-sided Scanning: 35/35 (300 x 300 dpi, send), 25.5/25.5 (600 x 600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA
Supported OS	Supported OS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV Optional: Super G3 FAX
Address Book	LDAP (2 000)/Local (1 600)/One-touch (200)
Send Resolution (dpi)	Push: (CL) up to 300 x 300/(BW) up to 600 x 600 Pull: (CL) up to 300 x 300/(BW) up to 600 x 600
Communication Protocol	FTP: (TCP/IP), SMB3.1.1(TCP/IP), WebDAV Email/iFax: SMTP(send), POP3(receive)
File Format	Standard: TIFF (MMR), JPEG ¹ , PDF (Compact, OCR (Text Searchable)), Optimise PDF for Web, Format to PDF/A-1b, Encrypt), XPS (Compact, OCR (Text Searchable)), PDF/XPS (Device Signature), Office Open XML (PowerPoint, Word) Option: PDF (Trace & Smooth), PDF/XPS (User Signature) ¹ Single-Page only.
FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultrafine), 200 x 400 (Superfine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Recording Size	Sending: A3, A4, A4R, A5 ¹ , A5R ¹ , B4, B5 ² , B5R ¹ Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R ¹ Sent as A4 ² Sent as B4 short
FAX Memory	Up to 30 000 pages (2 000 jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 addresses
Memory Backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power Source	220-240V, 50/60Hz, 5A
Power Consumption	Maximum: Approx. 1 500W Sleep Mode: Approx. 0.8W ¹ ¹ 0.8W is not available in all circumstances due to certain settings.
OTHER ACCESSORIES	
DADF-BA1, Platen Cover-Y3, Cassette Feeding Unit-AW1, Inner 2Way Tray-M1, Copy Tray-T2, Inner Finisher-L1, Inner 2/3 Hole Puncher-D1, Inner 2/4 Hole Puncher-D1, IC Card Reader Attachment-B4, Option Attachment Kit For Reader-A2, Utility Tray-B1, Media Adjustment Kit-A1, PS Printer Kit-CS1E, PCL International Font Set-A1E, PCL Asian Font Set-A1E, Barcode Printing Kit-D1E, Universal Send Trace & Smooth PDF Kit-A1E, Universal Send Digital User Signature Kit-C1E, Super G3 Fax Board-BN1, Remote Fax Kit-A1, Optional Data Storage Kit-A1, Copy Control Interface Kit-D1, ADF Access Handle-A1, Staple-P1	

Canon
Delighting You Always

CANON INDIA PVT. LTD.
7th Floor, Tower B, Building #5, DLF Epitome Building,
DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.

© 2023 Canon India Pvt. Ltd. All rights reserved. Printed in India.

Canon

Delighting You Always

imageRUNNER
2925 | 2930 | 2945

Swift Functionality for Smoother Workflows

Offering Streamlined Performance



Mobile
Support



Optimal
Security



Monochrome
Printing



USB
Compatible

Business Can Be Simple

imageRUNNER 2900 series

Introducing the new imageRUNNER 2900 series, a range of A3 monochrome multi-functional devices designed for small and medium-sized offices. Inheriting the high-end usability and functionality of the imageRUNNER ADVANCE DX line, the new series streamlines workflow and daily operations by simplifying operations with intuitive features.



Time-saving Accessibility

Combine different steps of day-to-day device operations, ranging from printing to encrypting documents, all into one personalised button. Simply customise multiple commonly used settings on the 177.8 mm (7 in) operating panel and execute them with ease, saving time and shortening work processes.

Swift Printing In Your Hands

Mobile printing and scanning is possible with the Canon PRINT Business application. Documents can be previewed and printed on mobile devices on the move by connecting them to your device via the QR code feature, improving printing accessibility in the workplace.

Template for Quick Printing

Printing templates can be set up with the Remote UI and customised into a button on the touch panel. Users can just click on the button to print commonly used templates without the need to access a PC.



Small Print & Storage Support



Documents can be stored on and printed from USB media storage without the need for a computer. Information on USB storage can be previewed on the multi-function device, preventing any accidental printouts of unwanted documents by users.



Trusted Data Security

Enhanced device security protects important documents and data, providing business with secured and safe experience.



IC Card



Pin Code

uniFLOW Online/Online Express

uniFLOW Online/Online Express prevents unauthorised users from using the machine through authentication, increasing document security.

Prevention Measures

Prevent execution of unauthorised applications through intelligent whitelisting. The multi-functional device allows only an approved list of applications to be activated, ensuring protection against malware and threats.



SPECIFICATIONS

MAIN UNIT	
Machine type	A3 Monochrome Laser Multifunctional
Core functions	Print, Copy, Scan, Send and Optional Fax
Control Panel	177.8 mm (7 in) TFT LCD WVGA Colour Touch panel
Memory	Standard: 2.0GB RAM
Storage	Standard: 64GB eMMC (available space 30GB) Optional: 256GB SSD
Interface Connection	Network Standard: 1000Base-T/100Base-TX/10Base-T, Wireless LAN (IEEE 802.11b/g/n) Others Standard: USB 2.0 (Host) x2, USB 2.0 (Device) x1
Paper Supply Capacity (A4, 80g/m ² (gsm))	Standard: 1200 sheets (100 sheets Multi-purpose tray, 2 x 550 sheets paper cassette) Maximum: 2300 sheets (with Cassette Feeding Unit-AW1)
Paper output capacity (A4, 80g/m ² (gsm))	Standard: 250 sheets Maximum: 645 sheets (with Inner Finisher-L1 and Copy Tray-T2)
Supported media types	Multi-purpose tray: Thin, Plain, Heavy, Recycled, Coated*, Colour, Tracing, Bond, Transparency, Labels, Pre-punched, Letterhead, Envelope, Postcard *SRA3 is unsupported for Coated (257 to 300g/m ² (gsm)) Upper/Lower Cassette: Thin, Plain, Heavy, Recycled, Colour, Bond, Transparency, Pre-punched, Letterhead, Envelope*, Postcard *Envelope Feeder Attachment Kit-A/B (standard) is required.
Supported media sizes	Multi-purpose tray: Standard size: SRA3, A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom size: 98.4 x 139.7 mm to 320.0 x 457.2 mm Free size: 100.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 98.0 x 98.0 mm to 320.0 x 457.2 mm Upper Cassette: Standard size: A4, A5, A5R, A6R, B5 Custom Size: 105.0 x 148.0 mm to 297.0 x 215.9 mm Envelopes: ISO-C5 Lower Cassette: Standard size: A3, A4, A4R, A5, A5R, A6R, B4, B5, B5R Custom Size: 105.0 x 148.0 mm to 304.8 x 457.2 mm Envelopes*: COM10 No.10, Monarch, DL *Envelope Attachment A (standard) is required.
Supported media weights	Multi-purpose tray: 52 to 300g/m ² (gsm) *SRA3 is unsupported for Coated (257 to 300g/m ² (gsm)), *Paper weight supported with Media Adjustment Kit-A1: 60-300g/m ² (gsm). Upper/Lower Cassette: 52 to 256 g/m ² (gsm) Duplex: 52 to 220g/m ² (gsm)
Warm-up Time (Quick start mode: ON)	4 s or Less* *Time from device power on to when copy icon appears and is enabled to operate on the touch panel display. From Sleep Mode: 10 s or less From Power On: 10 s or less* *Time from device power-on, until copy ready (not print reservation)
Dimensions (W x D x H)	With DADF-BA1 (IR2945): 565.0 x 687.0 x 891.0 mm With DADF-AZ2 (IR2930/2925): 565.0 x 693.0 x 852.0 mm
Installation Space (W x D)	Fully Configured: IR2945 1286 x 1116 mm (with DADF-BA1 + Inner Finisher tray max extended + Copy Tray-T2 max extended + paper cassette opened) IR2930/2925: 1286 x 1122 mm (with DADF-AZ2 + Inner Finisher tray max extended + Copy Tray-T2 max extended + paper cassette opened)
Weight	With DADF-BA1 (IR2945): Approx. 67 kg With DADF-AZ2 (IR2930/2925): Approx. 66 kg
PRINT SPECIFICATIONS	
Print Speed (BW)	IR2945: 1-sided: Up to 45 pages/min (A4), Up to 22 pages/min (A3), Up to 32 pages/min (A4R) IR2930: 1-sided: Up to 30 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R) IR2925: 1-sided: Up to 25 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R)
Print Resolution (dpi)	600 x 600, 1200 x 1200 (half-speed)
Page description languages	Standard: UFR II Option: Adobe PostScript 3, PCL6
Direct Print (RUI)	PDF, EPS, TIFF/JPEG, XPS
Printing from mobile and cloud applications	AirPrint, Mopria, Canon PRINT Business, uniFLOW Online and Universal Print
Fonts	PS fonts: 136 Roman PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ¹ (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ² ¹ Optional PCL International Font Set-A1 is required, ² Optional Barcode Printing Kit-D1 is required.
Operating System	UFR II: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS 10.13 or later PCL: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022 PS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022, macOS 10.13 or later PPD: Windows® 10/11, macOS 10.13 or later
COPY SPECIFICATIONS	
Copy Speed (BW/CL)	IR2945: 1-sided: Up to 45 pages/min (A4), Up to 22 pages/min (A3), Up to 32 pages/min (A4R) IR2930: 1-sided: Up to 30 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R) IR2925: 1-sided: Up to 25 pages/min (A4), Up to 15 pages/min (A3), Up to 20 pages/min (A4R)
First-Copy-Out Time (A4)	IR2945: 5.3 s IR2930/IR2925: 7.0 s

Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 9999 copies
Copy Density	Automatic or Manual (9 Levels)
Magnification	Variable zoom: 25% to 400% (1% Increments) Preset reduction/enlargement: 25%, 50%, 61%, 70%, 81%, 86%, 100% (1:1), 115%, 122%, 141%, 200%, 400%
SCAN SPECIFICATIONS	
Document Feeder Paper Capacity (80g/m ² (gsm))	DADF-BA1 (IR2945): up to 100 sheets DADF-AZ2 (IR2930/2925): up to 50 sheets
Acceptable originals and weights	Platen: Sheet, Book and 3-Dimensional objects Document Feeder media weight: DADF-BA1 (IR2945): 1-sided scanning: 38 to 128g/m ² (gsm) (BW), 64 to 128g/m ² (gsm) (CL) 2-sided scanning: 50 to 128g/m ² (gsm) (BW), 64 to 128g/m ² (gsm) (CL) DADF-AZ2 (IR2930/2925): 1-sided scanning: 38 to 128g/m ² (gsm) 2-sided scanning: 52 to 128g/m ² (gsm)
Supported media sizes	Platen: max. scanning size: 297.0 x 431.8 mm DADF-BA1 (IR2945): A3, A4, A4R, A5, A5R, B4, B5, B5R, B6 Custom size: 139.7 x 128.0 mm to 297.0 x 431.8 mm DADF-AZ2 (IR2930/2925): A3, A4, A4R, A5, A5R, B4, B5, B5R Custom size: 148.0 x 128.0 mm to 297.0 x 431.8 mm
Scan Speed (ipm: BW/CL; A4)	DADF-BA1 (IR2945): 1-sided Scanning: 70/70 (300 x 300 dpi, send), 51/- (600 x 600 dpi, copy) 2-sided Scanning: 35/35 (300 x 300 dpi, send), 25.5/- (600 x 600 dpi, copy) DADF-AZ2 (IR2930/2925): 1-sided Scanning: 35/25 (300 x 300 dpi, send), 25/- (600 x 600 dpi, copy) 2-sided Scanning: 12/8 (300 x 300 dpi, send), 8/- (600 x 600 dpi, copy)
Scan Resolution (dpi)	Scan for Copy: 600 x 600 Scan for Send (Push): 600 x 600 (SMB/FTP/WebDAV/IFAX), (Pull) 600 x 600 Scan for Fax: 600 x 600
Pull Scan Specifications	Colour Network ScanGear2. For both TWAIN and WIA
Supported OS	Supported OS: Windows® 10/11/Server2012/Server2012 R2/Server2016/Server2019/Server2022
SEND SPECIFICATIONS	
Destination	Standard: E-mail/Internet FAX (SMTP), SMB, FTP, WebDAV Optional: Super G3 FAX
Address Book	LDAP (2 000) / Local (1 600) / One-touch (200)
Send resolution (dpi)	Push: (CL) up to 300 x 300 (BW) up to 600 x 600 Pull: (CL) up to 300 x 300 (BW) up to 600 x 600
Communication protocol	FTP (TCP/IP), SMB3.1 (TCP/IP), WebDAV Email/Fax: SMTP(send), POP3(receive)
File Format	Standard: TIFF (MMR), JPEG, PDF (Compact, OCR (Text Searchable)), Optimise PDF for Web, Format to PDF/A-tb, Encrypt), XPS (Compact, OCR (Text Searchable)), PDF/XPS (Device Signature), Office Open XML (PowerPoint, Word) Option: PDF (Trace & Smooth), PDF/XPS (User Signature) *Single-Page only.
FAX SPECIFICATIONS	
Maximum Number of Connection Lines	1
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	200 x 100 dpi (Standard), 200 x 200 dpi (Fine) 200 x 400 dpi (Super Fine), 400 x 400 dpi (Ultra Fine)
Sending/Recording Size	Sending: A3, A4, A4R, A5, A5R, B4, B5, B5R ¹ Receiving: A3, A4, A4R, A5, A5R, B4, B5, B5R ¹ Sent as A4 ² Sent as B4 short
Fax Memory	Up to 30 000 pages (2 000 jobs)
Speed Dials	Max. 200
Group dials/destinations	Max. 199 dials
Sequential broadcast	Max. 256 addresses
Memory backup	Yes
ENVIRONMENTAL SPECIFICATIONS	
Operating Environment	Temperature: 10 to 30 °C Humidity: 20 to 80% RH (Relative Humidity)
Power Source	220-240V 50/60Hz 4A
Power Consumption	Maximum: Approx. 1,500W Sleep Mode: Approx. Wired LAN: 0.8W* * 0.8W is not available in all circumstances due to certain settings.
OTHER ACCESSORIES AND SUPPLIES	
Cassette Feeding Unit-AW1, Inner 2Way Tray-M1, Copy Tray-T2, Inner Finisher-L1, Inner 2/3 Hole Puncher-D1, Inner 2/4 Hole Puncher-D1, IC Card Reader Attachment-B4, Option Attachment Kit For Reader-A2, Utility Tray-B1, Media Adjustment Kit-A1, PS Printer Kit-BTIE, PCL International Font Set-A1E, Barcode Printing Kit-D1E, Universal Send Trace & Smooth PDF Kit-A1E, Universal Send Digital User Signature Kit-C1E, Super G3 Fax Board-BN1, Remote Fax Kit-A1, Optional Data Storage Kit-A1, Copy Control Interface Kit-D1, ADF Access Handle-A1, Staple-P1	



CANON INDIA PVT. LTD.
Corporate Office: 7th Floor, Tower B, Building #5,
DLF Eptome Building, DLF Phase III, Gurugram-122002
Ph.: 0124-4160000 | Fax: 0124-4160011 | Web: in.canon

DEALER'S STAMP

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximate. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim any liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.